



# PREMIER

## HIGH SECURITY SAFES

[USA: UL TL-30] [EU: ABIS GRADE 3]



MODEL PR3



# CMI SAFE CO.

Head Office: 244 West Street Carlton NSW 2218

Telephone: (02) 9547 1488 Fax: (02) 9547 2104

Website: <http://www.cmisafe.com.au> Email: [sales@cmisafe.com.au](mailto:sales@cmisafe.com.au)

**ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT AND TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.**

**CMI PREMIER T.D.R.:** The design of the safes and materials used provide defence barriers resisting to:

- **Oxy-Acetylene attack**
- **Drills and abrasive grinders**
- **Explosives and force**
- **Pneumatic and hydraulic tools**

**BODY:** The body gives a minimum thickness of 80mm of high density refractory materials at all points. These materials are bonded between inner and outer walls of specially reinforced steel, becoming a complete monolith after pouring. The engagement of the door and body effectively result in a continuous cube of exceptional strength and security.

**DOOR:** The door of the Premier safe has an overall thickness of 135mm, and the 55mm thick defensive slab section contains metals highly resistant to drills and abrasive grinders in addition to the high-strength poured barrier materials and other defences. The lockcase forms an integral part of the entire door structure, giving additional strength.

**BOLTWORK:** Heavy 32mm bolts provide 4 way locking into reinforced sections of the 2 sides, top and bottom of the safe body.

**INSURANCE COVER:** Insurance surveyors have suggested **\$100,000** as a realistic rating of overnight holding of cash and valuables in an unsupported situation.

**OPTIONAL:** 115mm high lockable roll-out drawer can be provided to secure in the bottom of Premier safes at additional



### MODEL PR3



AS/NZS 3809:1998

**ANCHORING:** 2 x 20mm recessed holes are provided in all models for anchor mounting to floor.

**LOCKING:** One La-Gard 6 digit electronic combination lock which secures the heavy duty 4 way locking 32mm bolt work, further supported by two automatic glass relockers. Powered by 1 x 9v alkaline battery.

A high quality key lock can be fitted as an optional extra if required at an additional cost.

**FINISH:** CMI Premier safes are available in attractive enamel hammertone durable finishes to suit any office decor. Satin finish handles, locks and fascia panels complement the high quality appearance.

**INTERNAL FITTINGS:** All models come standard with two adjustable shelves.

**FIRE RESISTANCE**  
The Premier safe has been designed to be fire resisting for one hour

MODEL	CODE	HEIGHT	WIDTH	DEPTH	WEIGHT kg	LITRES	LOCKING POINTS	PRICE
<b>PR1</b>	External	660 mm	560 mm	560 mm	<b>372</b>	<b>68</b>	<b>8</b>	\$
	Internal	508 mm	405 mm	330 mm				
<b>PR2</b>	External	770 mm	615 mm	660 mm	<b>500</b>	<b>122</b>	<b>8</b>	\$
	Internal	615 mm	457 mm	435 mm				
<b>PR3</b>	External	920 mm	615 mm	660 mm	<b>568</b>	<b>152</b>	<b>8</b>	\$
	Internal	762 mm	457 mm	435 mm				
<b>PR4</b>	External	1075 mm	660 mm	660 mm	<b>704</b>	<b>202</b>	<b>10</b>	\$
	Internal	910 mm	510 mm	435 mm				
<b>PR5</b>	External	1075 mm	765 mm	850 mm	<b>926</b>	<b>327</b>	<b>10</b>	\$
	Internal	910 mm	610 mm	585 mm				
<b>PR6</b>	External	1225 mm	765 mm	850 mm	<b>1026</b>	<b>381</b>	<b>10</b>	\$
	Internal	1066 mm	610 mm	585 mm				
<b>PR7</b>	External	1375 mm	765 mm	850 mm	<b>1128</b>	<b>435</b>	<b>12</b>	\$
	Internal	1220 mm	610 mm	585 mm				
<b>PR8</b>	External	1525 mm	765 mm	850 mm	<b>1230</b>	<b>489</b>	<b>12</b>	\$
	Internal	1370 mm	610 mm	585 mm				
<b>PR9</b>	External	1675 mm	765 mm	850 mm	<b>1345</b>	<b>542</b>	<b>12</b>	\$
	Internal	1520 mm	610 mm	585 mm				
<b>PR10</b>	External	1825 mm	765 mm	850 mm	<b>1464</b>	<b>595</b>	<b>12</b>	\$
	Internal	1675 mm	610 mm	585 mm				

(IMPORTANT: PLEASE ALLOW 55MM PROJECTION FOR DOOR FURNITURE ON DEPTH MEASUREMENT)

CMI Safe Co. reserve the right to alter specifications without notice or obligation.

To deliver and install level access metro INCL. GST

AVAILABLE FROM



CD BBF KB 09/02/2014

**MADE IN AUSTRALIA**